

Rinstrum Indicator Comparison

Model	Ingress Protection	# 350 Ohm load cells	Function inputs	Set Points	RS232 Ports	RS485 Ports	Inputs/Outputs	Networking	Clock Calendar	Custom Printing	Software	Analog Output	Unit Switching	Dual Range %	Products/Recipes	Check Weigh Bands	Hold & Peak Hold	Counting	Report Printing	Totalising Printing	Logic Setpoints	Batching	Materials	Speeds for Fill	Modbus ASCII	Profibus	Data Storage	Tilt Compensation	Ethernet	Truck Weighing	Summing, Master/Slave	Blue Tooth Serial Comms	Approvals										
R420 (ABS)	IP65	16	8	8	SA	S# A	32 I/O	S	S	***	K401	A	S	S	1	-	S	S	S	S	S	S	-	-	-	-	A	A	-	A	-	A											
												K402	A	S	S	S	250	-	S	S	S	S	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
												K404	-	S	S	S	250	-	-	-	S	S	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
R423 (Stainless Steel)	IP66	-	8	8	SA	S# A	32 I/O	S	S	***	K410	A	S	S	100	-	-	S	S	S	S	3 Stages	1	3	-	-	-	-	-	-	-	-	-										
												K411	A	S	S	100	-	-	-	-	S	S	10 Stages	6	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
												K491	A	S	S	250	-	S	S	S	S	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
R310	IP65	4	-	-	-	-	-	-	-	-	K301	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-								
												K302	-	S	S	S	-	-	S	S	S	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
R320/ R323	IP65	4~	1	2	1	A^	2 Out 1 In	S	S	*	K305	-	S	-	-	-	-	S	S	S	-	-	-	-	-	-	-	-	-	-	-	-	-	-									
												K304	-	S	S	S	-	-	S	S	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
X320	IP69K IP68	4~	1	-	1	A^	3 Out 1 In	S	S	*	K306	-	S	-	-	-	3	S	S	S	-	-	-	-	-	-	-	-	-	-	-	-	-	-									
												K304	-	S	S	S	-	-	S	S	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
2100	IP65	8	4	3	1	A^	3 I/O	-	S	*	-	-	S	-	1	3	S	S	S	-	S	S	1	2	-	-	-	-	-	-	-	-	-										
5000	8	4	4																																								
5100	8	5	6																																								
5200	IP65	12	4	4	2	1	4 Out S	S	S	**																																	
5230	12	4	4				4 In																																				
6700	-	4	4																																								
1203	IP65	6	1	2	1	1	2 Out 1 In	S	-	-																																	
N740	-	4	-	2	-	-	2 Out 1 In	S	-	-																																	
C740	-	-	-	-	-	-	-	-	S	-																																	



^ Convert RS232 port to RS485 with a 0080  
 # Transmit only  
 ~ 8x350ohm for non trade  
 % R400 Series Indicators are dual range & dual interval  
 @ K401/K402/K491/K481 use a maximum 8 input and 8 outputs of 32I/O

\* Basic custom printing  
 \*\* General custom printing  
 \*\*\* High level printing customisation

S Standard  
 A Accessory or Option

Approvals  
 1 NMI Australia  
 2 OIML R76  
 3 New Zealand  
 4 NMI S1/0