Rinstrum Indicator Comparison

	Model	Ingress Protection	No# 350 Ohm load cells	Function inputs	Set Points	RS232 Ports	RS485 Ports	Inputs/Outputs	Networking	Clock Calendar	Custom Printing	Software	Analog Output	Unit Switching	Dual Range %	Products/Recipes	Check Weigh Bands	Hold & Peak Hold	Counting	Report Printing	Totalising Printing	Logic Setpoints	Batching (stages)	Speeds for Fill	Materials	Modbus ASCII	Profibus	Data Storage	Tilt Compensation	Ethernet	Truck Weighing	Summing, Master/Slave	BlueTooth Serial Comms	Approvals	
	R420 (ABS)	IP65	16	8	8	S A	S# A	A 32 I/O @	S	S	***	K401	A	S	S	1	-	S	S	S	S	S	-	-	-	-	A	A	-	A	-	-	A	1,2,3	General
												K402	A	S	S	250	-	S	S	S	S	S	-	-	-	-	A	A	-	A	-	-	A		MultiProduct
												K404	-	S	S	250	-	-	-	S	S	S	-	-	-	-	A	A	-	A	S	-	A		Truck
	R423 (Stainless Steel)	IP66										K410	-	-	S	100	-	-	-	S	S	S	10	1	3	-	A	A	-	A	-	-	A		Fill
												K411	A	-	S	100	-	-	-	S	S	S	10	6	3	-	A	A	-	A	-	-	A		Batch
												K412	-	-	S	100	-	-	-	S	S	S	10	20	3	-	A	A	-	A	-	-	A		Batch
												K491	A	S	S	250	-	S	S	S	S	S	-	-	-	-	A	A	S	A	-	-	A	2	Tilt
			-									K481	A	-	-	250	-	-	-	S	S	S	-	-	-	-	A	A	-	A	-	S	A	4	Summing
	R310	IP65	4	-	-	-	-	-	-	-	-	K301	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	1,2,3	Basic
	R320/ R323	IP65	4~	1	2	1	A^	2 Out 1 In	S	S	*	K302	-	S	-	-	-	S	S	-	S	-	-	-	-	-	-	-	-	-	-	-	A	1,2,3	Single
												K305			S																				Dual
	X320	IP69K IP68	4~	1	-	1	A^	3 Out 1 In	S	S	*	K304	-	S	-	-	3	S	S	-	S	-	-	-	-	-	-	-	-	-	-	-	A	1,2,3	Single
												K306			S																				Dual
	2100	IP65	8	4	3	1	A^	3 I/O	-	S	*		-	S	-	1	3	S	S	-	S	-	S	1	2	-	-	-	-	-	-	-	A	1,2,3	General
	5000	IP65	8	4	4	2	1	6 Out 5 In	S	S	**		A	-	S	1	-	S	-	-	S	-	-	-	-	S	A	-	-	-	-	-	A	1,2,3	General
	5100		8	6	6										S	99	-	S	S	S	S	-	S	20	3	S	A	-	-	-	-	-	A	1,2,3	Batch
	5200		12	4	4			4 Out							S	99	5	S	S	S	S	-	-	-	-	-	-	-	-	-	-	-	A	1,2,3	Totalising Checkweigh
	5230		12	4	4			4 In							S	200	-	-	-	S	-	-	S	1	3	-	-	-	-	-	S	-	A	1,2,3	Truck
	6700		-	4	4										S	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	S	A	4	Summer/ Remote
	1203	IP65	6	1	2	1	1	2 Out 1 In	S	-	-		S	-	-	-	-	S	-	-	-	-	-	-	-	-	-	-	-	-	-	-	A	-	Weight Transmitter
	N740	-	4	1	2	-	-	2 Out 1 In	-	S	-		-	-	-	-	-	-	S	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	Load Cell
	C740		-																																Analogue

^	Convert RS232 port to RS485 with a 0080
#	Transmit only
~	8x350ohm for non trade
%	R400 Series Indicators are dual range & dual interval
@	K401/K402/K491/K481 use a maximum 8 input and 8 outputs of 32I/O

*	Basic custom printing
**	General custom printing
***	High level printing customisation

S	Standard
A	Accessory or Option

Approvals	
1	NMI Australia
2	OIML R76
3	New Zealand
4	NMI S1/0/A