Rinstrum Indicator Comparison

	Model	Ingress Protection	# 350 Ohm load cells	Function Inputs	Set Points	Inputs/Outputs	RS232 Ports	RS485 Ports	Clock Calendar Networking	Custom Printing	Software	Analog Output	Unit Switching	Dual Range %	Check Weigh Bands Products/Recipes	Hold & Peak Hold	Totalising Printing Report Printing Counting	Logic Setpoints	Batching (stages)	Speeds for Fill Materials	Modbus ASCII	Modbus TCP	Ethernet/IP	Data Storage	Tilt Compensation	Ethernet TCP	LUA Scripting	Truck Weighting	Sum Master/Slave	BlueTooth Serial	Approvals		
	C357	IP69K	8	3	-	-	-	A	S A	- -	S**	K301	-	S	S***	1	-	Manual	-	-	-	-	-	-	-	-	-	-	-	-	-	(A)	1,2,5	Standalone
				7	Basic (8) Adv (8)	4 in 4 out	2			S		K304					3	Manual + Peak	S		S						S							All Round
												K306	(A)																			Advanced
	C350	IP66		3	-	-	-			- -		K301	-				-	Manual	-														1,2,5	Standalone
				7	Basic (8) Adv (8)	4 in 4 out	2			S	S**	K304					3	Manual + Peak	S		S						S							All Round
												K306	(A)																			Advanced
	C327	IP69K		3	-	-	-			- -		K301	-				-	Manual	-		-						-						1,2,5	Standalone
				5	Basic (8) Adv (8)	2 in 2 out	2			S	S**	K304					3	Manual + Peak	S		S						S							All Round
												K306	(A)																			Advanced
	C320	IP65 αα		3	-	-	-			- -		K301	-				-	Manual	-		-						-						1,2,5	Standalone
				5	Basic (8) Adv (8)	2 in 2 out	2			S	S**	K304					3	Manual + Peak	S		S						S							All Round
												K306	(A)																			Advanced
	C520	IP65 αα	16	11	Adv (8)	A 8 I/O	S A	S A	S A	S	S*	K501	A	S	S	1	-	S	-	S	S	-	-	-	-	S	S	A	S	-	S	A	S	-	A	1,2,5	Process Control Truck Weighing
	C527	IP65																																
	C530	IP30		8			A	A																										
	R420	IP65 αα	16	8	8	A 32 I/O	S A	S# A	SA	S	S**	K401	A	S	S	1	-	S	S	S	S	S	-	-	-	-	-	-	A	-	A	A	-	-	A	1,2,3,5	General
												K402	A	S	S	250	-	S	S	S	S	S	-	-	-	-	-	-	A	-	A	A	-	-	A		MultiProduct
												K404	-	S	S	250	-	-	-	S	S	S	-	-	-	-	-	-	A	-	A	-	S	-	A		Truck
												K405	-	S	S	250	-	-	-	S	S	S	-	-	-	-	-	-	A	-	A	-	S	-	A		Static Axle
	R423	IP66 αα										K410	A	-	S	100	-	-	-	S	S	S	10	1	3	-	-	-	A	-	A	A	-	-	A		Fill
												K411	A	-	S	100	-	-	-	S	S	S	10	6	3	-	-	-	A	-	A	-	-	-	A		Batch
												K412	A	-	S	100	-	-	-	S	S	S	10	20	3	-	-	-	A	-	A	-	-	-	A		Batch
	R427	IP66										K422	-	S	S	250	-	S	-	S	S	S	-	-	-	-	-	-	A	-	A	A	S	-	A	-	Dynamic Axle
												K491	A	S	S	250	-	S	S	S	S	S	-	-	-	-	-	-	A	S	A	A	-	-	A	2	Tilt
			-									K481	A	-	-	250	-	-	-	S	S	S	-	-	-	-	-	-	A	-	A	-	-	S	A	4	Summing
	R320/ R323	IP65 αα	4~	-	-	-	-	-	-	-	-	K342			S			Manual	-	-	-													-		Basic
						1 in						K344								-	-															+RS232 Comms
					2^							K346								-	-															+IO
				1		1 in 2 out	S	A^	S	S	S*	K354	-	S	-	-	-	-	S	S	-	-	-	-	-	-	-	-	-	-	-	-	A	1,2,3,5	+Clock+Custom Print
												K356						C	C																	+SetPoint
					2^^							K356-C1						Manual/Peak	-																	Maual/ Peak hold
												K356-C2						Manual	-		S															Livestock
												K356-C3						.	S																	Counting
												K356-C4						Manual/Peak	-																	Medical hold
	X320	IP69K IP68	4~	1	-	3 Out 1 In	S	A^	S	S	S*	K376	-	S	-	1	3	C	C	S	S	-	-	-	-	-	-	-	-	-	-	-	A	1,2,3,5	Check weighing
			-			-		-				K376-LIVE	-	-	-	-	-	Manual	-																	Manual hold and Livestock
	5000	IP65 αα	12	4	4	4 In + 4 Out	2	S	S	S	S*		A	-	S	1	-	S	-	-	S	-	-	-	-	S	-	-	-	-	-	-	A	1,2,3	General
	5100			6	25										S	99	-	S	S	S	S	-	S	20	3	S	-	-	-	-	-	-	-	A		Batch
	5200			4	4										S	99	5	S	S	S	S	-	-	-	-	-	-	-	-	-	-	-	-	A		Totalising Checkweigh
	5230			4	4										S	200	-	-	-	S	-	-	S	1	3	-	-	-	-	-	-	S	-	A		Truck
	6700		-	4	4										S	-	-	-	-	-	S	-	-	-	-	-	-	-	-	-	-	S	A	4	Summer/Remote (Rinstrum,Avery,Gedge,A&D,Toledo,Barlo,Lodec,Phillips 1577, 1627)
	1203-D	IP65	6	1	2	1 In + 2 Out	S	S	S	-	-		S	-	-	-	-	S	-	-	-	-	-	-	-	-	-	-	-	-	-	-	A	-	Weight Transmitter

^	Convert RS232 port to RS485 with a 0080
#	Transmit only
~	8x350ohm for non trade
%	R400 Series Indicators are dual range & dual interval
αα	Indicators achieve this IP ratings from the front only when correctly panel mounted
^	Basic Over/ Under Setpoints
^^	Advanced Set Points
*	Custom printing
**	Advance custom printing
***	triple range

S	Standard	C – Cross Grade	
A	Accessory or Option	C1 – K356-PEAK (R300-572)	
(A)	exclude ethernet TCP	C2 – K356-LIVE (R300-573)	
##	Bluetooth & wifi	C3 – K356-COUNT (R300-574)	
		C4 – K356-MED (R300-575)	

Approvals		
	1	NMI Australia
	2	OIML R76
	3	New Zealand
	4	NMI S1/0/B
	5	NTEP (III/III L)